

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier
KRONES colclean CG 1001
Article number: 0903431495, 0903073464, 0903073462, 0903073335
1.2 Relevant identified uses of the substance or mixture and uses advised against
1.2.1 Relevant uses

Chain lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet
Company

KIC KRONES Internationale Cooperationsgesellschaft mbH
 Böhmerwaldstraße 5
 93073 Neutraubling / GERMANY
 Phone +49 9401 70-3020
 Fax +49 9401 70-3696
 Homepage www.kic-krones.com
 E-mail kic@kic-krones.com

Address enquiries to
Technical information

kic@kic-krones.com

Safety Data Sheet

sdb@chemiebueero.de

1.4 Emergency telephone number
Advisory body

+49 (0)89-19240 (24h) (english)

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture

Eye Dam. 1: H318 Causes serious eye damage.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

Signal word

DANGER

Contains:

Neutralization product from (Z)-N-9-octadecenylpropane-1,3-diamine with formic acid *)

Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER / doctor.

2.3 Other hazards
Human health dangers

Irritant gases/vapours.

If swallowed or in the event of vomiting, risk of product entering the lungs.

Environmental hazards

The product/the substance has the Water Hazard Class 2.

Other hazards

Further hazards were not determined with the current level of knowledge.

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
3 - < 10	Neutralization product from (Z)-N-9-octadecenylpropane-1,3-diamine with formic acid *) CAS: 7173-62-8 / 64-18-6, EINECS/ELINCS: 230-528-9 / 200-579-1 GHS/CLP: Skin Irrit. 2: H315 - Eye Dam. 1: H318 - Aquatic Acute 1: H400
1 - < 5	Propan-2-ol CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0, Reg-No.: 01-2119457558-25-XXXX GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336

Comment on component parts

*) This substance is a completely dissociated ion mixture according to Annex V REACH. Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%. For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air.
Skin contact	In case of contact with skin wash off immediately with plenty of water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a doctor immediately.
Ingestion	Get medical advice. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
If swallowed or in the event of vomiting, risk of product entering the lungs.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	foam, dry powder, water spray jet, carbon dioxide
Extinguishing media that must not be used	Full water jet

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.
Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Use personal protective equipment.
High risk of slipping due to leakage/spillage of product.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.
In case the product spills into drains/surface waters/groundwater, immediately inform the authorities.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, universal absorbent, diatomaceous earth).
Dispose of absorbed material in accordance with the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

The normal safety precautions for handling chemicals must be observed.
Avoid contact with eyes and skin. Use personal protective equipment.

Do not eat or drink when working.
Take off contaminated clothing and wash before reuse.
Wash hands before breaks and after work.
Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Keep container tightly closed.
Keep container in a well-ventilated place.
Keep in a cool place. Store in a dry place.

7.3 Specific end use(s)

See product use, SECTION 1.2

SECTION 8: Exposure controls / personal protection
8.1 Control parameters
Ingredients with occupational exposure limits to be monitored (GB)

Substance
Propan-2-ol
CAS: 67-63-0, EINECS/ELINCS: 200-661-7, EU-INDEX: 603-117-00-0, Reg.No.: 01-2119457558-25-XXXX
Long-term exposure: 400 ppm, 999 mg/m ³
Short-term exposure (15-minute): 500 ppm, 1250 mg/m ³

DNEL

Substance
Propan-2-ol, CAS: 67-63-0
Industrial, inhalative, Long-term - systemic effects: 500 mg/m ³ .
Industrial, dermal, Long-term - systemic effects: 888 mg/kg.
general population, inhalative, Long-term - systemic effects: 89 mg/m ³ .
general population, dermal, Long-term - systemic effects: 319 mg/kg.
general population, oral, Long-term - systemic effects: 26 mg/kg kg/d.

PNEC

Substance
Propan-2-ol, CAS: 67-63-0
sewage treatment plants (STP), 2251 mg/l.
freshwater, 140,9 mg/l.
sediment (freshwater), 552 mg/kg.
sediment (seawater), 552 mg/kg.
seawater, 140.9 mg/l.
soil, 28 mg/kg.

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Tightly fitting goggles. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,11 mm, Butyl rubber, >480 min (EN 374-1/-2/-3). > 0,11 mm, Nitrile rubber, >480 min (EN 374-1/-2/-3). > 0,11 mm, >480min, PVC (EN 374-1/-2/-3).
Skin protection	Long-sleeved work clothes.
Other	Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	Not required under normal conditions.
Thermal hazards	not applicable
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	colourless yellowish
Odor	characteristic
Odour threshold	No information available.
pH-value	4-6
pH-value [1%]	No information available.
Boiling point [°C]	ca. 100
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	not applicable
Upper explosion limit	not applicable
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	No information available.
Density [g/ml]	ca. 0,98
Bulk density [kg/m³]	not applicable
Solubility in water	completely miscible
Partition coefficient [n-octanol/water]	No information available.
Viscosity	No information available.
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	ca. 0
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	No information available.

9.2 Other information

No information available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

No hazardous reactions known.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No dangerous reactions known if used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Substance
Propan-2-ol, CAS: 67-63-0
LD50, dermal, Rabbit: 6410 mg/kg.
LD50, dermal, Rat: 4570-5840 mg/kg.
LD50, oral, mouse: 3600 mg/kg (RTECS).
LC50, inhalative, Rabbit: 30 mg/l/4h.
LC50, inhalative, Rat: 30-73 mg/l/4h.

Serious eye damage/irritation	Risk of serious damage to eyes. Calculation method
Skin corrosion/irritation	Based on the available information, the classification criteria are not fulfilled.
Respiratory or skin sensitisation	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Propan-2-ol, CAS: 67-63-0
LC50, (96h), Pimephales promelas: 9640 mg/l.
LC50, (48h), Leuciscus idus: 8970 mg/l (DIN 38412, 15).
EC50, (72h), Scenedesmus subspicatus: > 100 mg/l (Lit.).
EC50, (24h), Daphnia magna: > 1000 mg/l (DIN 38412, 11).
EC10, Pseudomonas putida: 5175 mg/l (DIN 38412).

12.2 Persistence and degradability

Behaviour in environment compartments	No information available.
Behaviour in sewage plant	No information available.
Biological degradability	No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.
Coordinate disposal with the authorities if necessary.

Waste no. (recommended)

070601*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended)

150102
150110*

SECTION 14: Transport information**14.1 UN number**

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011). CHIP 3/ CHIP 4

- **Observe employment restrictions for people** Observe employment restrictions for young people.

- **VOC (2010/75/CE)** ca. 1,6 %

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Hazard statements (SECTION 03)

H400 Very toxic to aquatic life.
 H318 Causes serious eye damage.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.
 H319 Causes serious eye irritation.
 H225 Highly flammable liquid and vapour.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Classification procedure

Eye Dam. 1: H318 Causes serious eye damage. (Calculation method)

Modified position

SECTION 7 been added: Take off contaminated clothing and wash before reuse.

SECTION 7 been added: Avoid contact with eyes and skin. Use personal protective equipment.

SECTION 8 been added: Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.

SECTION 9 been added: No information available.

SECTION 9 deleted: not determined

SECTION 11 been added: Based on the available information, the classification criteria are not fulfilled.

SECTION 11 deleted: not determined

SECTION 11 been added: Calculation method

SECTION 11 been added: Risk of serious damage to eyes.

SECTION 11 deleted: not determined

SECTION 12 been added: No information available.

SECTION 12 deleted: not determined

Copyright: Chemiebüro®

