

Technical Data Sheet

KRONES creadditive FIL PS 01

Glue stick

Product description and application

The KRONES creadditive FIL PS 01 glue stick makes sure prints stick firmly when the print-bed is hot and then releases as soon as it cools down. This unique and innovative mechanism means that no tools are needed to remove prints from the bed. They just pop off when the bed cools down.

1. Shake the KRONES creadditive FIL PS 01 pen
2. Press the nib (end of your pen) on the printing bed for KRONES creadditive FIL PS 01 to flow and spread the adhesive evenly on the printing area (cover your bed with an even thin layer)
3. Make sure that no spots are missed

It's best to apply KRONES creadditive FIL PS 01 when the printing bed is still cold, but it will also work when the printing bed is already hot.

Compatible with:

- KRONES creadditive FIL 10 02
- KRONES creadditive FIL 11 01
- KRONES creadditive FIL 11 02
- KRONES creadditive FIL 12 01
- KRONES creadditive FIL 13 01

Technical product data

Density	-
Color	Transparent to milky
Print temperatur	-
Heat bed	-
Fan speed	-
Print speed	-

Storage and shelf life

Please store the glue stick at 15 – 25 °C in its originally sealed package in a clean and dry environment. If the recommended storage conditions are observed the products will have a minimum shelf life of 12 months. After opening the original packaging, the glue stick must be used within 6 months.

Material safety data sheets

The current material safety data sheets are available for you to download from our website:

www.kic-krones.com/en/downloads.php

You are also welcome to request them by e-mail to kic@kic-krones.com.

Labelling

Please refer to the corresponding material safety data sheet for details on:

- Hazardous goods labelling (section 2)
- Transport regulations (section 14)
- Safety regulations (section 4-8)

Cleaning

Use a damp cloth to wipe off all the glue residues until a clean surface is visible. Wipe again with after rinsing the cloth with water.

Product safety

Recommended: Process materials in a well-ventilated room or use professional extraction systems. For further and more detailed information please consult the corresponding material safety data sheets.

Exclusion of liability

To the best of our knowledge, the information reflects today's know-how and experience of the Krones Group and does not include any guarantee of features, nor does it guarantee the suitability of the product for specific purposes. Legal liability cannot be deduced from information provided or from oral consultation. This product information is not subject to the updating service. It is mandatory to carry out a test run and an inspection of the features before the products are used.

Status: 12/2021