

Technical data sheet

KRONES colclean AD 2002**Defoamer****Product description and application**

KRONES colclean AD 2002 is a defoamer for all kinds of caustic detergent solutions (i.e. bottlewashing, CIP, crate washing, spray wash applications).
KRONES coclean AD 2002 is surfactant based and for use above 40°C. Efficacy is at its best when the mixing with the cleaning solution is most intensive (dosing at the pressure side of the pump).
KRONES colclean AD 2002 is free of silicones. For industrial use only.

Operating conditions

Concentration:	30-120ppm or 30-120ml/m ³ cleaning solution
Dosing:	automatically, in combination with caustic or machine cycle
Temperature:	40 to 95°C
Contact time:	permanent

Concentration check

Only via consumption

Physical data

Form/colour/smell:	liquid, colourless, specific
pH value:	approx. 7
Density:	approx. 0.99 g/cm ³
Flash point:	> 100°C
Foaming:	defoaming
Temperature stability:	stable at 0 to +40°C
Conductivity (in deionised water):	-

Material compatibility

Compatible in the working concentration with all common materials in food industry like: Stainless steel, glass, PET, PE, PP, PVC, PVDF, PTFE, Viton, EPDM.
At the same time, however, the possibility of material incompatibilities cannot be completely ruled out. We recommend to carry out appropriate tests in case of uncertainty.

Storage/ Shelf life

The product should be stored sealed in the original container in a cool, well ventilated place.
Minimum shelf life: 2 years.

Classification

Please refer to the corresponding safety data sheet for details on:
Hazardous Information
Transport Regulations
Safety Regulations

Disposal

Recycling of packaging only fully emptied and closed.
Any product residues must be disposed of in accordance with local regulations. For further information, please refer to our safety data sheet.

Further information

Ingredients according to EC regulation 648/2004

>=30%: non-ionic surfactants

See EC safety data sheet

Special instructions

Rinse with sufficient amount of drinking water, to avoid any residues on surfaces, which could come into contact with foodstuff.

Due to possible incompatibilities with other products, it is recommended to rinse dosing equipment (pumps, pipes) thoroughly with water prior to a change-over to KRONES colclean AD 2002.

This version of the technical data sheet supersedes all previous versions, which thereby become invalid.

All information and recommendations are based to the best of our knowledge on the latest state of the art in technology and our experience and do not constitute a contractual relationship. All references to DIN standards are for product description purposes only and do not constitute a guarantee.

Processing and material quantities need to be adjusted to account for local conditions. In the event of problems, please seek technical advice. Subject to changes.