

## Technical data sheet

**KRONES Hydrocare 200****Scale Inhibitor****Product description and application**

KRONES Hydrocare 200 is specially designed to inhibit scale formation in RO-systems with polyamide, cellulose acetate and polyether membranes with negative charged surface. KRONES Hydrocare 200 is a stabilized blend of low molecular weight polymers with a high dispersing effect. It is the most effective inhibitor against calcium sulphate and calcium carbonate deposit on the membrane surface. Also barium and strontium sulphate are stabilized excellently.

KRONES Hydrocare 200 is designed and approved as a highly efficient scale inhibitor for use with cellulose acetate and polyamide membranes. There is no interaction with the membrane material. The dosage is controlled proportionally to the feed water flow. Standard metering pumps are used. Fitting materials are PE, PP or coated steel. It is recommended to inject KRONES Hydrocare 200 undiluted. The required dosage level depends on the operating conditions and water composition and varies in the range of 1 to 10 ppm as delivered.

KRONES Hydrocare 200 is easy to be handled and does not contain any aggressive component. The pH value of the product is neutral. For industrial use only.

**Operating conditions**

|                |                                |
|----------------|--------------------------------|
| Concentration: | 1 to 10ppm (mg/l)              |
| Dosing:        | proportional to the water flow |
| Temperature:   | given                          |

**Concentration check**

Via water consumption

**Physical data**

|                    |                               |
|--------------------|-------------------------------|
| Form/colour/smell: | clear, slightly yellow liquid |
| pH value:          | 7.0 to 7.5                    |
| Density:           | 1.19 to 1.21g/cm <sup>3</sup> |
| Freezing point:    | - 23°C                        |
| Boiling range:     | <100°C                        |
| viscosity:         | approx. 250 mPas              |

**Material compatibility**

Compatible with all common materials in food industry like: Stainless steel, glass, PET, PE, PP, PVC, PVDF, PTFE, Viton, EPDM.

At the same time, however, the possibility of material incompatibilities cannot be completely ruled out. We recommend to carry out appropriate tests in case of uncertainty.

**Storage/ Shelf life**

The product should be stored sealed in the original container in a cool, well ventilated place.

The storage temperature should be between +2°C and 30°C.

Minimum shelf life: 2 years.

**Classification**

Please refer to the corresponding safety data sheet for details on:

Hazardous Information

Transport Regulations

Safety Regulations

**Disposal**

Recycling of packaging only fully emptied and closed.

Any product residues must be disposed of in accordance with local regulations. For further information, please refer to our safety data sheet.

**Further information**

See EC safety data sheet

**Special instructions**

Due to possible incompatibilities with other products, it is recommended to rinse dosing equipment (pumps, pipes) thoroughly with water prior to a change-over to KRONES Hydrocare 200.

---

This version of the technical data sheet supersedes all previous versions, which thereby become invalid.

All information and recommendations are based to the best of our knowledge on the latest state of the art in technology and our experience and do not constitute a contractual relationship. All references to DIN standards are for product description purposes only and do not constitute a guarantee.

Processing and material quantities need to be adjusted to account for local conditions. In the event of problems, please seek technical advice. Subject to changes.